

UltrafixCircular Spacers

What is Ultrafix?

Conac's Ultrafix Circular Spacers are designed for use in civil precast and commercial construction applications. The unique design offers 360 degrees of cover. The built-in sleeves prevent the circular spacer from twisting when in position, holding the bar firmly in place.

The central clip in the Ultrafix model also locks the reinforcement, so it stops it from falling out even if the Ultrafix rotates against the formwork as the reinforcement is lowered. The circular spacer provides the same level of concrete cover, irrespective of the bar diameter in use.



Why are Ultrafix Circular Spacers popular?

Circular spacers, like Ultrafix, also go by the names wagon wheels, fast wheels, circulars or pile cage spacers. Circular spacers provide support in raked pile applications, where a reinforcing mesh or rebar is placed in a vertical position.

For example, circular spacers are designed to be used when lowering cages into pile holes or trenches. By clipping the circular spacer on to the cage, they keep the cage correctly spaced as it is lowered into the trench.

CONAC's Ultrafix Circular Spacer will not twist out of the desired position, thereby ensuring your reinforcing steel is positioned exactly where you need it.

Fields of Application

- · Civil Precast and Commercial Construction
- Columns and piers
- · Bar spacers in conduit

Availability Chart

Code	Cover (mm)	Material	Min Bar Size (mm)	Max Bar Size (mm)
34UFIX15.410	15	Plastic	4	10
34UFIX20.410	20	Plastic	4	10
34UFIX30.410	30	Plastic	4	10
34UFIX20.516	20	Plastic	5	16
34UFIX25.516	25	Plastic	5	16
34UFIX30.516	30	Plastic	5	16
34UFIX35.516	35	Plastic	5	16
34UFIX40.516	40	Plastic	5	16
34UFIX50.516	50	Plastic	5	16

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by Conac are based upon records, tests, or experience that Conac believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any Conac or third party intellectual property rights is granted or implied with this information. Product Selection and Use: Many factors beyond Conac's control and uniquely within user's knowledge and control can affect the use and performance of an Conac product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., AS, Work Safe etc.). Failure to properly evaluate, select, and use an Conac product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property. Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specificable Conac product packaging or product literature (in which case such warranty governs), Conac warrants that each Conac product meets the applicable Conac product specification at the time Conac ships the product. Conac MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a Conac product does not conform to this warranty, then the sole and exclusive remedy is, at Conac's option, replacement of the Conac product or refund of the purchase price. Limitation of Liability: Except for the li

www.conac.com.au Issue Date: 02/2023 1300CONAC1